



**Part Number :** [1301530286](#)


**Product Description :** Super-Safeway In-Line Industrial GFCI, IP69K, Portable, Single Phase, Manual Reset, Flying Leads (Primary), Y-Splice to (2) NEMA 5-20 Watertite Extreme Receptacles (Secondary), 20A, 120V, 12/3 SOOW Cord, 0.61m (2.0') Cord Length

**Series Number :** 130153

**Status :** Active

**Product Category :** Power Distribution

**Engineering Number :** 20052-Y-2MH



NO IMAGE AVAILABLE

---

## Documents & Resources

### Drawings

[1301530286\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Power Distribution
Series	130153
Description	Super-Safeway In-Line Industrial GFCI, IP69K, Portable, Single Phase, Manual Reset, Flying Leads (Primary), Y-Splice to (2) NEMA 5-20 Watertite Extreme Receptacles (Secondary), 20A, 120V, 12/3 SOOW Cord, 0.61m (2.0') Cord Length
Enclosure Rating	NEMA 4X
NEMA Configuration	NEMA 5-20
Product Name	Super-Safeway
Type	GFCI Industrial Duty, Single Phase
UPC	78172562565

### Agency

UL	E66308
----	--------

### Electrical

Current - Maximum per Contact	20.0A
GFCI	Yes-In-line
GFCI Reset	Manual
Ground Continuity Monitor	No
Open Neutral Relay	Yes
Voltage - Maximum	120V, 240V

### Physical

Cord Diameter	15.11mm (.595")
Cord Grip Body Size	N/A
Cord Length	0.61m (2.0')
Cord Type	12/3 SOOW
Feed-Thru	Yes
Flip Lid	No

Material - Housing	Nylon
Mounting Style	Portable
Number of Receptacles	2 - Y-Splice
Packaging Type	Carton
Receptacle Type	GFCI Dual

---

This document was generated on Mar 27, 2025